

## CAN-CONTROL

## **CAN ADAPTER FOR CAR SHARING SOLUTIONS**

Teltonika CAN-CONTROL is the latest addition to CAN Solutions family, it allows remote doors and windows closing control, which is ideal for car sharing and mobility solutions for car rentals, car sharing providers and corporate fleet management providers.

CAN-CONTROL can read not only such essential CAN parameters like: fuel level, odometer, VIN number, fuel consumption, but also can read engine RRM, engine temperature or handbrake status. This way you can effectively identify areas of improvement within your vehicle operation to drive down overheads and minimize environmental impact.



## **USE CASES**















## **Technical data**

Input voltage range 9 - 16 V DC  Power consumption At 12V < 23,6 mA (Standby) At 12V < 23,5 mA (Working)  Operating temperature range -40°C to +85°C  Operating humidity Max 85 % non-condensing  LED indication 1 status LED light  Central lock control Windows closure Turn lights control Trunk release Door status Lock status Handbrake status Lights status Vehicle range Vehicle driven distance Total fuel consumption Fuel level (dashboard) Engine speed (RPM) Vehicle speed  For electric cars: Battery level Charging status Charging status Vehicle range on battery  *Data and control functions are available depending on vehicle's equipment, model, type and manufacture year.	recilinear data	
Power consumption  At 12V < 23,6 mA (Standby) At 12V < 23,5 mA (Working)  Operating temperature range  -40°C to +85°C  Operating humidity  Max 85 % non-condensing  LED indication  1 status LED light  Central lock control Windows closure Turn lights control Trunk release Door status Lock status Lock status Handbrake status Lights status Vehicle range Vehicle driven distance Total fuel consumption Fuel level (dashboard) Engine speed (RPM) Vehicle speed  For electric cars: Battery level Charging status Charging cable status Vehicle range on battery  *Data and control functions are available depending on vehicle's equipment, model, type and manufacture year.	Supported by	FMB1YX, FM36YX, FMB64X series
At 12V < 23,5 mA (Working)  Operating temperature range -40°C to +85°C  Operating humidity Max 85 % non-condensing  LED indication 1 status LED light  Central lock control Windows closure Turn lights control Trunk release Door status Lock status Handbrake status Lights status Vehicle range Vehicle driven distance Total fuel consumption Features*  Fuel level (dashboard) Engine speed (RPM) Vehicle speed  For electric cars: Battery level Charging status Charging cable status Vehicle range on battery  *Data and control functions are available depending on vehicle's equipment, model, type and manufacture year.	Input voltage range	9 - 16 V DC
Operating humidity  Max 85 % non-condensing  LED indication  1 status LED light  Central lock control Windows closure Turn lights control Trunk release Door status Lock status Handbrake status Lights status Vehicle range Vehicle driven distance Total fuel consumption Fuel level (dashboard) Engine speed (RPM) Vehicle speed  For electric cars: Battery level Charging status Charging cable status Vehicle range on battery  *Data and control functions are available depending on vehicle's equipment, model, type and manufacture year.	Power consumption	
LED indication  1 status LED light  Central lock control Windows closure Turn lights control Trunk release Door status Lock status Handbrake status Lights status Vehicle range Vehicle driven distance Total fuel consumption Features* Features*  For electric cars: Battery level Charging status Charging cable status Vehicle range on battery  *Data and control functions are available depending on vehicle's equipment, model, type and manufacture year.	Operating temperature range	-40°C to +85°C
Central lock control Windows closure Turn lights control Trunk release Door status Lock status Handbrake status Lights status Vehicle range Vehicle driven distance Total fuel consumption Features* Fuel level (dashboard) Engine speed (RPM) Vehicle speed  For electric cars: Battery level Charging status Charging cable status Vehicle range on battery  *Data and control functions are available depending on vehicle's equipment, model, type and manufacture year.	Operating humidity	Max 85 % non-condensing
Windows closure Turn lights control Trunk release Door status Lock status Handbrake status Lights status Vehicle range Vehicle driven distance Total fuel consumption Features* Fuel level (dashboard) Engine speed (RPM) Vehicle speed  For electric cars: Battery level Charging status Charging cable status Vehicle range on battery  *Data and control functions are available depending on vehicle's equipment, model, type and manufacture year.	LED indication	1 status LED light
Differsions STX 30 X TO THILL (EX W X TI)	Features*	Windows closure Turn lights control Trunk release Door status Lock status Handbrake status Lights status Vehicle range Vehicle driven distance Total fuel consumption Fuel level (dashboard) Engine speed (RPM) Vehicle speed  For electric cars: Battery level Charging status Charging cable status Vehicle range on battery  *Data and control functions are available depending on vehicle's equipment, model, type and manufacture year.
	Dimensions	51 x 36 x 16 mm (L x W x H)